
## **HEPP 100 (Master Pin Pusher)**

## SAFE Removal and Installation of Track pins, Master pins, Bushings and Master bushings

## **Package Includes:**

- 1. Hydraulic Cylinder: Double acting 100t capacity x 350 mm stroke, working pressure 700 bar
- 2. "C" frame: for holding the track links attached to the hydraulic cylinder with 2 Nos. tie-rods.
- 3. 20t cap x 12mm stroke flat Jack Model OSF 20-12 fitted with female coupler to split links.
- 4. Pin set tooling which consist of following (Extra charges will be applied)\*
  - Forcing Pin: 1 No
  - Pushing Pin: 1 No
  - Centering Spacers (aligning bush): 2Nos.- for locating and supporting the pushing pin.
  - aligning Adaptor: 1 No. To properly support the track link.
  - Set of fixed spanners and Allen key set
- 5. Safety guard
- 6. Telescopic Tripod with 0.5 ton chain pulley block and sling with safety hook.
- 7. Spare seal kit for cylinder.
- 8. Set of fixed spanners and Allen key set
- 9. Carrying case



The offered equipment is suitable for installing and removing pins of following sizes.

Min Dia (mm)	Max Dia (mm)	Min Length	Max. Length (mm)
		(mm)	
19.3	60.2	160	320

<sup>\*</sup>Pin set tooling to be confirmed depending on the number of track make/models and extra charges will be applied